

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau



(43) International Publication Date  
15 March 2001 (15.03.2001)

PCT

(10) International Publication Number  
WO 01/17854 A1

(51) International Patent Classification<sup>7</sup>: B65B 11/58 (81) Designated States (national): AE, AG, AL, AM, AT, AT (utility model), AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CR, CU, CZ, CZ (utility model), DE, DE (utility model), DK, DK (utility model), DM, DZ, EE, EE (utility model), ES, FI, FI (utility model), GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SK (utility model), SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.

(21) International Application Number: PCT/IE00/00104

(22) International Filing Date: 8 September 2000 (08.09.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: S990763 9 September 1999 (09.09.1999) IE

(71) Applicant (for all designated States except US): COM-  
TOR LIMITED [IE/IE]; 51/52 Fitzwilliam Square,  
Dublin 2 (IE).

(72) Inventor; and

(75) Inventor/Applicant (for US only): LACEY, Liam, J.  
[IE/IE]; The Moorings, Merrion Road, Ballsbridge, Dublin  
4 (IE).


(74) Agents: SHORTT, Peter, Bernard et al.; Tomkins & Co.,  
5 Dartmouth Road, Dublin 6 (IE).

Published:

- With international search report.
- With amended claims.

For two-letter codes and other abbreviations, refer to the "Guid-  
ance Notes on Codes and Abbreviations" appearing at the begin-  
ning of each regular issue of the PCT Gazette.

(54) Title: A WRAPPING METHOD AND APPARATUS



WO 01/17854 A1

(57) Abstract: The invention concerns a method and apparatus for wrapping loads (1) of goods and materials in a wrapping material, such as a plastics film, which comprises placing at least two battens in a spaced substantially parallel orientation on one surface of the load, partially wrapping the load in a wrapping material by rotating the load relative to dispensing means for the wrapping material and/or rotating the dispensing means around the load, to envelop the battens in the wrapping material and to hold the battens in place on the surface of the load, the battens being placed apart to support the load and being adapted to receive therebetween the forks of a fork-lift truck for transporting the load. Preferably, the wrapping material overlaps the ends of the battens to hold the battens in position. The load is then turned through about 90° from a first wrapping station (4) to a second wrapping station (7), where the wrapping is completed. The apparatus includes a first wrapping station (4) having a wrapping platform to receive the load (1) to be wrapped, a pick end place unit (3) at the first wrapping station (4) for placing battens on a surface of the load (1), wrapping material dispensing means at the first wrapping station, means for rotating the platform relative to dispensing means, and/or means for rotating the dispenser relative to the platform, to partially wrap the load (1), including at least part of the battens, with the wrapping material, transfer means (6) the load (1), through about 90° to a second wrapping station (7), and means at the second wrapping station (7) for completing the wrapping of the load (1).